

DESCRIPTION

IMPROVING GREY SCALE CONTRAST IN A 3D IMAGE DISPLAY DEVICE

The present invention relates to display devices, and in particular to display devices adapted to display three dimensional or stereoscopic images.

5

The generation of three-dimensional images generally requires that a display device is capable of providing a different view to the left and the right eye of a user of the display device. This can be achieved by providing a separate image directly to each eye of the user by use of specially constructed goggles. In one example, a display provides alternating left and right views in a time sequential manner, which views are admitted to a corresponding eye of the viewer by synchronised viewing goggles. In contradistinction, the present invention relates to classes of display devices where different views of an image can be seen according to the viewing angle relative to a single display panel. Hereinafter, these will be referred to generally as 3D display devices.

15

One known class of such 3D display devices is the liquid crystal display in which the parallax barrier approach is implemented. Such a system is illustrated in figure 1.

With reference to figure 1, a display device 100 of the parallax barrier type comprises a back panel 11 that provides a plurality of discrete light sources. As shown, the back panel 11 may be formed by way of an areal light source 12 (such as a photoluminescent panel) covered with an opaque mask or barrier layer 13 having a plurality of slits 14a to 14d distributed across its surface. Each of the slits 14 then acts as a line source of light.

25

A liquid crystal display panel (LCD) 15 comprises a plurality of pixels (eg. numbered 1 to 10 in figure 1) which are separately addressable by electrical signals according to known techniques in order to vary their respective light transmission characteristics. The back panel 11 is closely positioned with respect to the LCD panel 15 such that each of the line sources 14 of light corresponds to a group 16 of pixels. For example, pixels 1 to 5

30

shown as group 16₁ correspond to slit 14a, pixels 6 to 10 shown as group 16₂ correspond to slit 14b, etc.

Each pixel of a group 16 of pixels corresponds to one view V of a plurality of possible views (V_{-2} , V_{-1} , V_0 , V_1 , V_2) of an image such that the
5 respective line source 14a can be viewed through one of the pixels 1 to 5 corresponding to that view. The number of pixels in each group 16 determines the number of views of an image present, which is five in the arrangement shown. The larger the number of views, the more realistic the 3D effect becomes and the more oblique viewing angles are provided.

10 Throughout the present specification, we shall refer to the 'image' being displayed as the overall image being generated by all pixels in the display panel, which image is made up of a plurality of 'views' as determined by the particular viewing angle.

A problem exists with this prior art arrangement. The light transmission
15 coefficient of each pixel in the LCD panel is strongly dependent upon the viewing angle. Thus, if all pixels 1 to 5 are driven equally, the viewed intensity of source 14a will appear different for different views. For example, V_0 will be different than V_2 . Thus, the viewed intensity of the source will appear different for different viewing angles.

20 Conventionally, the perceived intensity of the viewed source for any particular element in an image is an important function of properly rendering grey scales in the image. A conventional display device will provide drive signals to each pixel of a display panel so as to vary its transmission coefficient such that a desired grey scale level is achieved for that element of
25 the image. For the 3D display device described above, if each pixel 1 – 5 is driven at the same voltage, corresponding to the required grey scale for that element of the image, the resulting grey scale image will be a function of viewing angle. This results in a sub-optimal image and unwanted grey scale artefacts when observing the different views of the image.

30

It is an object of the present invention to overcome or mitigate the unwanted grey scale artefacts in a display device for displaying three

dimensional images in which different views of the image are displayed according to the viewing angle.

According to one aspect, the present invention provides a display
5 device for displaying a three dimensional image such that different views are displayed according to the viewing angle, the display device including:

a display panel having a plurality of separately addressable pixels for displaying said image, the pixels being grouped such that different pixels in a group correspond to different views of the image;

10 a display driver for controlling an optical characteristic of each pixel to generate a grey scale image according to received image data; and

a grey scale compensation device for further controlling said optical characteristic of at least some pixels within a group to compensate for a predetermined viewing angle dependency of said optical characteristic.

15 According to another aspect, the present invention provides a method for displaying a three dimensional image on a display device such that different views of the image are displayed according to the viewing angle, the method comprising the steps of:

processing image data to form grey scale pixel data values for each one
20 of a plurality of separately addressable pixels in display panel, the pixels being grouped such that different pixels in a group correspond to different views of the image, the pixel data values each for controlling an optical characteristic of a respective pixel to generate a grey scale image;

applying grey scale correction values to at least some pixel data values
25 within each group to compensate for a predetermined viewing angle dependency of the optical characteristic; and

using the corrected pixel data values to drive pixels of a display panel to generate said image.

30 Embodiments of the present invention will now be described by way of example and with reference to the accompanying drawings in which:

Figure 1 shows a schematic cross-sectional view of an existing design of LCD device that uses the parallax barrier approach to display three dimensional images;

Figure 2 shows a schematic cross-sectional diagram useful in illustrating the geometry of a parallax barrier LCD device;

Figure 3 shows a transmission versus voltage curve for a 90 degree twisted nematic LCD for viewing angles of $\phi = 0$ degrees (ie. normal to the plane of the display) and for $\phi = 50$ degrees;

Figure 4 shows a schematic block diagram of a display device according to embodiments of the present invention;

Figure 5 shows an embodiment of the invention utilising a lenticular array;

Figure 6 shows an alternative form of light source suitable for use with the display device; and

Figure 7 shows a graph of viewing angle properties of a conventional liquid crystal display panel useful in illustrating display optimisation principles in accordance with the present invention.

With reference to figure 1, the basic function of a parallax barrier type, three dimensional image display device has already been described. A similar structure of display panel 15 and back panel 11 illumination source may be used in the preferred embodiment of the invention. However, it will be recognised that other configurations may be used as will become evident hereinafter.

In general, the invention uses a display panel 15 having a plurality of separately addressable pixels 1...10, in which the pixels are grouped so that the different pixels 1...5 or 6...10 respectively in a group 16₁ and 16₂ correspond to different views of the image. The display panel 15 may be any suitable electro-optical device in which an optical characteristic of each pixel can be varied according to an electrical control signal to generate an image. Preferably the display panel is a liquid crystal display.

An illumination source having a plurality of discrete light sources 14a ... 14d, so that each group 16 of pixels is positioned to receive light from a respective one of the light sources, is preferably provided. This may be by way of the areal light source 12 and mask 13 arrangement of figure 1, but
5 could also be provided by way of a pixellated light source providing light sources 14 as lines of pixels, individual pixels or blocks of pixels.

Still further, the plurality of discrete light sources could be virtual light sources provided by way of a backlight and lens array (e.g. a lenticular sheet array) providing a series of high intensity light spots. Such an arrangement is
10 illustrated in figure 6. A display device 80 includes an LCD panel 75, areal light source 72 and a lens array 71. The lens array focuses light from the areal source 72 into a plurality of discrete focal points 73 just outside the plane of the LCD panel so that each illuminates a plurality of pixels in the LCD panel, similar to that described in connection with figure 1.

15 Part of a group of pixels in the display panel 15 is shown in figure 2. A light source 14 of width w corresponds with, and can be viewed through, a group of pixels 0...7 at respective viewing angles $\phi_0, \phi_1, \dots \phi_7$ relative to the normal of the plane of the display panel. It will be understood that only half of the pixel group 16 is shown, a further seven pixels being present to the left of
20 pixel 0 to complete the pixel group 16.

Each pixel has a width $p_0, p_1, \dots p_7$. Preferably, widths $p_0 \dots p_7$ are equal, but they could vary in order to compensate to a certain extent for the angle of incidence of light passing therethrough. The distance between the back panel illumination source 14 and the display panel 15 is shown as h . In a preferred
25 display device, $h = 2.3$ mm, $p_0 = 200$ microns, and $w = 50$ microns although these values may be varied significantly.

Figure 3 shows transmission (T) versus voltage (V) characteristics 30 for a display panel 15 in the form of a 90 degree twisted nematic LCD. The first curve 31 (solid line) is the T - V characteristic for a viewing angle $\phi = 0$ degrees (e.g. pixel 0). The second curve 32 (broken line) is the T - V
30 characteristic for a viewing angle $\phi = 50$ degrees (e.g. pixel 5). It will be noted that the variation in transmission coefficient for a pixel viewed at $\phi = 0$ is such

that to obtain a suitable grey scale range an operating voltage of between 0 and V_1 is suggested, depending on the grey scale value required to be displayed. However, it will be noted that use of the same voltage range to drive pixel 5 will result not only in a different set of grey scale values for a given drive voltage, but even a grey scale inversion in that the slope of the T-V characteristic is reversed.

In accordance with the invention, it is thus proposed to use a different range of driving voltages for pixel 5 ($\phi = 50$ degrees), namely that portion lying between V_1 and V_2 , so that the T-V characteristic for pixel 5 is more closely matched to that of pixel 0.

More generally, an appropriate portion of the T-V characteristic may be selected for each viewing angle ϕ_0 to ϕ_7 (or for as many angles as are present in the display panel).

Yet more generally, compensation may be made for the variations in slope of the different T-V characteristics of each viewing angle.

Where the T-V characteristics of two different viewing angles are sufficiently close, a common voltage range and/or compensation may be made for those two viewing angles.

The present invention therefore provides a grey scale compensation device that controls the optical characteristic of each pixel 0...7 in a group 16 so as to compensate for the viewing angle.

The grey scale compensation device preferably substantially normalises a grey scale displayed by a group 16 of pixels to that of the other pixels in the group for any given location in the display panel. The perceived grey scale rendering thereby becomes independent of the viewing angle.

Different grey scale correction factors will be required for different display types and for transmissive versus reflective displays. Appropriate grey scale correction factors can be determined from appropriately generated transmission / reflection coefficients determined according to techniques known to the person skilled in the art.

Figure 4 shows schematically exemplary embodiments of a display device 101 incorporating a grey scale compensation device.

An image processor 50 receives a stream of image information including grey scale pixel data for each of a plurality of views $\phi_0 \dots \phi_7$. The image information is processed and stored into a frame buffer 51 in digital form so that it can be rendered onto a display device 53. Frame buffer 51 includes
5 a plurality of pages 58, each page including the pixel data for a respective view, $\phi_0, \phi_1, \dots \phi_7$.

The frame buffer 51 is accessed by a display driver 52 that provides appropriate drive voltage and/or current signals to each pixel of a display panel 53 in accordance with each of the stored values in frame store 51. As a
10 general principle, it will be understood that the application of grey scale correction values by a grey scale compensation device can be applied either:

- (i) by digitally modifying the image data stored in the frame store 51 to include a correction factor so that the value of drive parameter selected by the display driver 52 is suitably modified, or
- 15 (ii) by leaving the image data stored in the frame store 51 unmodified, but applying a correction factor to the output of the display driver 52.

In a first embodiment, a grey scale compensation device 60 (shown in dashed outline) is provided as, for example a look-up table accessible by the
20 image processor 50. The look-up table comprises a plurality of pages 61, 62, 63 of correction values, each page corresponding to one of the viewing angles $\phi_1 \dots \phi_7$ to be applied to image data received by the image processor. The image processor 50 obtains appropriate corrections to the image data and stores this compensated data in frame store 51.

25 The expression 'correction values' in this context may include 'substitution' values or 'offset' values. In other words, for a given input pixel value x_i , the look-up tables 61 – 63 may provide a substitution value x_s (as a function of ϕ) to be stored in the frame store in place of x_i . Alternatively, for a given input pixel value x_i , the look-up tables 61 – 63 may provide an offset
30 value x_o (as a function of ϕ) which is combined with the input value and the result $x_i + x_o$ stored in the frame store in place of x_i .

A particular advantage of this embodiment is that it can be implemented with very little, if any, change in hardware from a conventional LCD driver arrangement. The functions of the image processor 50 can be realised in software, and the functions of the grey scale compensation device 60 can also
5 be realised as a software implementation.

In a variation on this first embodiment, the compensation device 60 may operate independently of the image processor 50 upon data already stored in the frame store 51 by the image processor 50. This can be effected by using a second access port 64 to the frame store 51. The compensation device 60 in
10 this embodiment may also be implemented as a software module, without interfering with the operation of the image processor 50 (for example, where this is a customised graphics processor). Again, the look-up tables 61 – 63 may provide a substitution value or an offset value to be implemented by the grey scale compensation device.

15 In a second embodiment, it is recognised that the grey scale compensation for each pixel drive signal could be carried out in real time in the analogue domain, i.e. by applying a correction voltage offset to each pixel signal produced by the display driver 52. Thus, in this embodiment, a grey scale compensation device 70 is installed between the display driver 52 and
20 the display panel 53 to apply specific offset voltages and/or currents to those output by the display driver. In this arrangement, the grey scale correction values may be considered as voltage and/or current offset values.

For the sake of completeness, it is also noted that a hybrid system could deploy both techniques of digital correction values applied to the frame
25 store 51 by compensation device 60 and analogue offsets applied to the display driver outputs by compensation device 70. An appropriate contribution would be made by both, although this may be a more complicated solution. For example, analogue offsets or correction values applied by the grey scale compensation device 70 might be selected to move the operation of the
30 display panel into an appropriate portion of the transmission-voltage characteristic 30, while digital correction values might be selected to

compensate for differences in the slope of the transmission-voltage characteristics.

It is also noted that the grey scale compensation device 60 as described herein may also be applied in other forms of 3D display other than that shown in figures 1 and 2. With reference to figure 5, it will be noted that the invention
5 can also be applied to a lenticular 3D display device 200. In this lenticular display device, a liquid crystal display panel 115 includes a plurality of pixels (a_1 to a_8 are shown) arranged in groups 116₁, 116₂, in similar manner to that in figure 1. On top of the LCD array 115 is positioned a lenticular array 120 of
10 cylindrical lenses 121, 122. The lenticular array may include any sheet of corrugated optical material, or array of discrete or joined lenses to provide localised focusing for groups of pixels of the LCD panel.

In the arrangement shown in figure 5, the width of each lens element is chosen to be eight pixels, corresponding to an eight-view 3D display. Of
15 course, the width of each lens element may be chosen to correspond to different numbers of pixels according to the angular resolution required. The pixels a_1 to a_8 of the LCD are imaged into the different views. For example, the light rays emitted from pixels a_2 and a_4 are shown. One sees that in the
LCD substrate 116, the rays emitted by pixel a_2 propagate to a large extent
20 obliquely with respect to the rays emitted by pixel a_4 . The angle between them is, on average, approximately equal to the angle between the two views (θ).

It will be seen that in a lenticular-type 3D display device, the light rays of the different views travel through the liquid crystal layer at different angles. Therefore, the problem of grey scale dependency of the angle still exists, and
25 is solved by the grey scale compensation device 70 as described in connection with figure 4.

The invention as described above also has important implications for the optimisation of liquid crystal displays generally. The viewing angle dependence of LCD panels is known generally to be rather poor. Figure 7
30 illustrates how contrast and grey scale inversion depends upon viewing angle for a standard 90 degree twisted nematic (TN) transmissive LCD without compensation foil. The horizontal viewing angle is shown on the x-axis

between -60 degrees and $+60$ degrees from the normal to the plane of the display, and the vertical viewing angle is shown on the y-axis between -60 degrees and $+60$ degrees from the normal to the plane of the display.

The orientations of the optical axes 90, 91 of the LCD polarisers and the
5 optical axes 92 of the liquid crystal directors are shown in the lower part of the figure.

From figure 7, it is seen that the image quality strongly depends upon viewing angle. For the example shown in figure 7, the optimal viewing angles are represented by the diagonal line 94 running from top left to bottom right,
10 and grey scale inversion occurs for viewing positions to the right and above the line 94.

Conventionally, for most important applications such as televisions and computer monitors, it is recognised that maximising performance for horizontal viewing directions is more important than maximising performance for vertical
15 viewing directions. For example, for television applications, multiple viewers of a display device will normally be arranged with their eye levels more-or-less consistent relative to the screen (i.e. with very little variation along the y-axis), but their horizontal viewing angles relative to the x-axis may vary significantly. Similarly, a user seated at a computer monitor is more likely to vary head
20 position along the x-axis while working, than along the y-axis.

According to convention, therefore, the LCD would be rotated anticlockwise through 45 degrees from the orientation shown in figure 7, such that its polarisation axes are at approximately 45 degrees to the x- and y-axes of the display when in use. In this way, the performance of the display device
25 is optimised for horizontal viewing angles, but is compromised for vertical viewing angles.

3D LCD displays suffer from the same problems with optimisation of viewing angle dependency in respect of x and y directions.

30 However, in the present invention, it is recognised that optimisation of grey scale rendering can be achieved by electronic techniques in driving the

display, using the described grey scale compensation device 60 and/or 70 as described above.

Therefore, it is more appropriate to provide the display device with an orientation in which the inherent optical characteristics of the display panel are optimised for vertical viewing angle variations. Horizontal viewing angle variations are accommodated for and optimised using the electronic driving techniques as described herein.

Thus, in a preferred arrangement, the 3D display device described above is arranged so that, in normal use, it has the pixels within each group 16 that provide different views as a function of angle to a first axis of the display panel, and has the polarising elements of the display panel oriented so as to minimise viewing angle dependence relative to a second axis of the display, where the second axis is orthogonal to the first axis.

In a most general sense, the inherent optical characteristics of the display panel are such that viewing angle dependence is reduced or substantially minimised relative to the y-axis and the grey scale compensation device 60 and/or 70 serves to reduce or substantially minimise viewing angle dependence relative to an axis that is transverse to the y-axis. More preferably, the grey scale compensation device 60 and/or 70 serves to reduce or substantially minimise viewing angle dependence relative to an axis that is orthogonal to the y-axis (i.e. the x-axis). In a most preferred device, the x-axis is defined as the horizontal axis when the display is in normal use, and the y-axis is defined as the vertical axis when the display is in normal use.

Other embodiments are intentionally within the scope of the accompanying claims.